

APPENDIX FOR GOODS HOIST

Goods Hoist Particular

1.	OWNER Name & Address :	
2.	GENERAL Rated Load: Total Travel: No. of Stops/Openings Control: Drawing No.	REMARKS Maximum of 2 tons Maximum of 12 m
3.	HOIST Model: Manufacturer: Serial No.: Speed (m/min): Capacity (kg): Power (KW): Year Built: Hoist Supporting Beam Specification:	1.25 x (SWL + Dead Load)
4.	SUSPENSION Rope or Chain: Type of Roping/Chain: Rope Diameter and Construction: Terminal Connections: Safety Factor:	Minimum 7
5.	CAGE Size (W x D x L): Area (m ²): Construction: Type of Door: Warning Sign: Overload Switch:	Maximum 3.5m ² (internal cage area, without any cladding)

6.	<p>VERTICAL PASSAGEWAY AND LANDINGS</p> <p>Vertical Passageway Enclosure: Cage and Vertical Passageway Clearance (mm): Clearance Between Edge of Landing Threshold and Cage Platform Nosing (mm): Type of Landing Door: Openings in Gate or Grille: Landing Door Height: Landing Door Interlock: Guide rail rest:</p>	<p>Maximum opening 12.7 mm Minimum of 100 mm 20 (min) - 40 (max) mm</p> <p>Maximum of 51 mm Minimum of 1676 mm</p>
7.	<p>SAFETY FEATURES</p> <p>Governor: Type of Safety Gear: Type of Buffer: Upper & Lower Final Termination Stops: Cage and Hoist Tower Electrically Grounded: Phase Failure or Reverse Phase Safety Device:</p>	
8.	<p>OTHERS:</p>	